

2.0-Ton R-32, 3-Port Heat Pump, Ductless ODU 3MXM24AVJU9

FEATURES

High-efficiency inverter driven swing compressor

BENEFITS

12 Year limited parts warranty with online registration



Submittal Date: 11/3/2025 10:49:43 AM

Page 1 of 0



2.0-Ton R-32, 3-Port Heat Pump, Ductless ODU 3MXM24AVJU9

EFFICIENCY				PERFORMANCE				
	SEER2	EER2	HSPF2	COP	coc	COOLING: HEATING:		TING:
Non-Ducted:	21.00	12.00	10.00		Rated (Btu/hr):	23,000	Rated (Btu/hr):	24,000
Ducted:					Operating Range:	14°F - 115°F	Operating Range:	5°F - 60°F
Mixed:	10.50	6.00	5.00	0	Rated Cooling Conditions:		Rated Heating Conditions:	
					Indoor (°F DB/DB): 80 / 67 Ambient (°F DB/WB): 95 / 75		Indoor (°F DB/WB): 70 / 60 Ambient (°F DB/WB): 47 / 43	

ELECTRICAL		PIPING			
Power Supply (V/Hz/Ph): *See Engineering Manuals for other voltages.	*208-230 / 60 / 1	Max. System Piping Length: (feet):	230	Gas Conn. (inch):	3/8
System MCA: (Min.circuit amps)	19.9	Max. Interunit Piping Length: (feet):	230	Liquid Conn. (inch):	1/4
System MFA: (Max.fuse amps)	25.0	Max. Height Difference IDU to ODU (feet):	49.25	Drain Conn. (inch):	5/8
Compressor RLA: (Rated load amps)	17.0	Max. Height Difference IDU to IDU (feet):			
Outdoor fan motor FLA: (Full load amps)		Refrigerant Pre-Charged Pipe Length (ft):	131.25		
Outdoor fan motor W: (Rated output watts)	150.0				

SPECIFICATIONS				
Compressor Type: Swing		Compressor Stage:	Inverter	
Refrigerant Type:	R-32	Refrigerant Oil:	PVE (FVC50K)	
Factory Charge (Lbs):	4.9	Additional Refrigerant Charge (Ozs/ft):	0.22	
COOLING - Airflow Rate (cfm):		HEATING - Airflow Rate (cfm):		
High:	2,462	High:	2,140	
Med:	2,055	Med:	2,140	
Low:	1,939	Low:	1,070	
Sound Level (dBA):	52	Sound Level (dBA):	54	
Dimensions (HxWxD) (in):	29-1/2 x 34-1/4 x 12-5/8	Net Weight (lb):	140	

Daikin North America LLC, 19001 Kermier Rd, Waller, TX 77484

www.daikinac.com www.daikincomfort.com

Daikin City Generated Submittal Data

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)


Submittal Date: 11/3/2025 10:49:43 AM Page 2 of 0



2.0-Ton R-32, 3-Port Heat Pump, Ductless ODU 3MXM24AVJU9

DIMENSIONAL DRAWING

3MXM24AVJU9



3D149808



2.0-Ton R-32, 3-Port Heat Pump, Ductless ODU 3MXM24AVJU9

ACCESSORIES

PART NUMBER	DESCRIPTION	INCLUDED
KEH064A41	Drain Pan Heater	No
KPS063A41	Snow hood (intake side plate) (15, 18 & 24)	No
KPS063A44	Snow hood (intake rear plate) (15,18 & 24)	No
KPS063A47	Snow hood (outlet) (15, 18 & 24)	No
KPW063B4	Air direction adjustment grille	No

Page 4 of 4