

PROJECT NAME _____

LOCATION _____


ARCHITECT _____

ENGINEER _____

CONTRACTOR _____

REFERENCE _____

SUBMITTED BY _____ DATE _____

Indoor Unit (IDU): DRADL0612F2A	Outdoor Unit (ODU): DRA1H09S2A	Wired Thermostat: DRSTAT101
		

PRODUCT FEATURES

- Up to 100% heating capacity at 0°C
- Low ambient cooling and heating down to -22°F
- Variable Speed Inverter Compressor
- A2L refrigerant detection system
- Horizontal and vertical installation
- External drain pump included (in horizontal installation only)
- Static pressure up to 0.4 in. WC
- DRSTAT101 programmable wired thermostat included
- Turbo, ECO, Sleep modes and more
- Quiet operation
- Included base pan heater
- Anti-corrosive fin coating

CAPACITIES		
Cooling Capacity (BTU/hr)	Rated at 95°F (35°C) ¹	9000
	at 109°F (43°C)	11100
	at 5°F (-15°C)	13200
	Cooling Range	3400~13500
Heating Capacity (BTU/hr)	Rated at 47°F (8°C) ²	12500
	Rated at 17°F (-8°C) ³	9600
	Rated at 5°F (-15°C) ⁴	11200
	at -13°F (-25°C)	7600
	at -22°F (-30°C)	6400
	Heating Range	3800~16200

SYSTEM DATA

Refrigerant Type	R-454B
Refrigerant Charge (oz. (kg))	35.3 (1.0)
Design Pressure (PSIG)	550/340
Indoor/ Outdoor Coil Coating	Golden Fin Coating

EFFICIENCY DATA

SEER2	21.4
EER2	13.4
HSPF2	12.5
COP at 47°F (8°C) ²	3.53
COP at 17°F (-8°C) ³	2.50
COP at 5°F (-15°C) ⁴	1.89

Specifications are subject to change without notice.

© 2024 Ferguson Enterprises LLC

www.durastar.com



Intertek



9,000 BTU/H LOW STATIC DUCTED HEAT PUMP SYSTEM

SPECIFICATIONS

LINE SET REQUIREMENTS	
Connection Type	Flare
Liquid (in. (mm))	Ø1/4 (Ø6.35)
Gas (in. (mm))	Ø3/8 (Ø9.52)
Pre-Charge Length (ft. (m))	25 (7.5)
Minimum Length (ft. (m))	10 (3.0)
Maximum Length (ft. (m))	82 (25.0)
Maximum Height Differential (ft. (m))	33 (10.0)
Additional Refrigerant (oz./ft (g/m))	0.16 (15)

OUTDOOR UNIT		
Unit Dimensions	Width	31-3/4 (805)
	Depth	13 (330)
	Height	21-13/16 (554)
Carton Dimensions	Width	36 (915)
	Depth	14-5/8 (370)
	Height	24-1/4 (615)
Net Weight (lbs. (kg))	72.8 (33.0)	
Gross Weight (lbs. (kg))	78.7 (35.7)	
Cooling Operating Temp. (°F (°C))	-22 - 122 (-30 - 50)	
Heating Operating Temp. (°F (°C))	-22 - 75 (-30 - 24)	
Voltage/Phase/Frequency	208-230V, 1 Phase, 60 Hz	
Voltage Range	187-253V	
Recommended Breaker (Amps)	15	
Minimum Circuit Ampacity (Amps)	15.0	
Communication Wire Size	14*4 AWG Stranded	
Rated Current - Cooling (Amps) ¹	3.4	
Rated Current - Heating (Amps) ²	4.5	
Sound Pressure (dB(A))	56	

¹ Value at AHR1 Rated Capacity at 95°F (35°C) (AFull)

² Value at AHR1 Rated Capacity at 47°F (8°C) (H1Full)

³ Value at AHR1 Rated Capacity at 17°F (-8°C) (H32)

⁴ Value at AHR1 Rated Capacity at 5°F (-15°C) (H42)







INDOOR UNIT		
Unit Dimensions (in. (mm))	Width	27-9/16 (700)
	Depth	19-15/16 (506)
	Height	7-7/8 (200)
Carton Dimensions (in. (mm))	Width	33-7/8 (860)
	Depth	21-5/16 (540)
	Height	11-1/4 (285)
Net Weight (lbs. (kg))	39.5 (17.9)	
Gross Weight (lbs. (kg))	46.7 (21.2)	
Indoor Unit Air Flow (CFM (m³/h))	Silent	118 (200)
	Low	177 (300)
	Medium	265 (450)
	High	324 (550)
	Turbo	400 (680)
Static Pressure (in. WC (Pa))	0 - 0.4 (0 - 100)	
Moisture Removal (Pints/day (L/h))	35.5 (0.7)	
Field Supplied Drain Pipe O.D. (in. (mm))	Ø1 (Ø25)	
Drain Pump Lift (in. (mm))	21-5/8 (550)	
Recommended Breaker (Amps)	15	
Minimum Circuit Ampacity (Amps)	3.0	
Sound Pressure (dB(A))	Silent	23
	Low	30
	Medium	31
	High	33

COMPRESSOR	
Type	DC Rotary Inverter
Oil Type	Ester Oil VG74
Oil Charge (oz. (ml))	11.8 (350)



Specifications are subject to change without notice.

© 2024 Ferguson Enterprises LLC


www.durastar.com




Ceiling mount clearances




Wall mount (vertical) clearances




Maintenance access panel clearance



Clearances



Dimensions



NOTE

Illustrations in this document are for explanatory purposes. The actual shape of your mini-split equipment may vary slightly.