

SUBMITTAL - 12KUAS1R

Job Name: _____

Date: _____

Location: _____

R32

Indoor Unit: **ARUH12KUAS**

Outdoor Unit: **AOUH12KUAS1**



FEATURES

INDOOR UNIT:

- Mid Static Duct indoor unit delivering superior comfort and energy-efficient performance
- Indoor unit with ProCore™ (High Corrosion Resistant Copper) coils for long-lasting protection against corrosion
- Whisper-quiet operation with sound levels as low as 24dB
- Multiple fan speed options; Auto, High, Med, Low, and Quiet
- Special Operation modes available:
 - Economy Mode/ Energy Saving Mode / Powerful Mode / Minimum Heat Mode / Automatic defrosting operation / Auto-restart function
- Enhanced controls platform for seamless, intuitive operation:
 - Seamless control using the optional IR Receiver and Wireless Remote Controller kit (UTY-LBTUM)
 - Optional Wi-Fi connectivity enables remote monitoring through the Airstage Mobile App
 - Extended connectivity with support for third-party interface options
 - Compatible with BACnet and Modbus protocols for seamless integration with Building Management and Home Automation Systems
- Advanced scheduling and timer options offer greater control over unit operation:
 - Weekly Timer / 24-hr Timer / Sleep Function
- Built-in drain pump for efficient water removal making installation and maintenance easier
- Features automatic static pressure detection for optimal airflow and system efficiency
- Wide external static pressure range of up to 0.8 inWG for adaptable performance
- Offers group control, allowing seamless management of multiple units simultaneously
- Equipped with a built-in refrigerant leak detection sensor for enhanced safety and reliability.
- Additional premium features include, but are not limited to:
 - Built-in external input and output for interlocking systems with 3rd party devices (Ex: Fire Alarm, Door Switch, Humidifier, Aux. Heat & more)
 - Supports compatibility with the Airzone third-party communicating zoning system for optimized zoning control
 - Multiple Auxiliary Heat logic options for optimized heating performance
 - Service monitoring functionality via compatible accessories (UTY-RVRU & UTY-RNRUZ-series)
 - Flexible intake configuration with side or bottom options to meet installation requirements.

OUTDOOR UNIT:

- Low GWP R-32 systems for reduced environmental impact
- INVERTER-driven compressor that offers superior performance, comfort, and energy savings
- Compact outdoor unit with extended line set lengths up to 98ft (30m)
- Up to 33% higher rated heating capacity than nominal capacity
- Provides low ambient cooling and heating down to -5°F for dependable performance in extreme conditions.



7 Year Compressor, 5 Year Parts out-of-the-box Warranty.



10 Year Compressor, 10 Year Parts Warranty when registered within 60 days of installation in a residence.



12 Year Compressor, 12 Year Parts Warranty when registered within 60 days of installation in a residence and installed by a Fujitsu Elite contractor.



SUBMITTAL - 12KUAS1R

SPECIFICATIONS:

Indoor Unit					ARUH12KUAS	
Outdoor Unit					AOUH12KUAS1	
System Name					12KUAS1R	
AHRI Number					215434556	
SEER2		Cooling			Btu/hW	19.1
EER2						12.7
HSPF 2 (IV) / HSPF 2 (V)		Heating				kW/kW
COP2					3.76	
Outdoor Operation Range		Cooling			°F (°C)	-5 to 122* ⁸ (-21 to 50* ⁸)
		Heating				-5 to 75 (-21 to 24)
Indoor Capacity		Cooling		Rated	Btu/h	12000
				Min.—Max.		3,100—13,600
		Heating	47°FDB (Outdoor temp.)	Rated		16000
				Min.—Max.		3,400—19,400
			17°FDB (Outdoor temp.) ¹	Rated		10700
				Max.		17300
			5°FDB (Outdoor temp.) ²	Rated		15500
			Max.			
Outdoor Connection pipe	Size	Liquid			in (mm)	Ø1/4 (Ø6.35)
		Gas				Ø3/8 (Ø9.52)
	Method					FLARE
	Pre-charge length			ft (m)	66 (20)	
	Min. length				16 (5)	
	Max. length				98 (30)	
	Max. height difference				49 (15)	
Indoor Dimensions (H × W × D)		Net			in (mm)	11-13/16 × 27-9/16 × 27-9/16 (300 × 700 × 700)
		Gross				15-3/4 × 36-15/16 × 34-7/16 (400 × 938 × 875)
Indoor Weight		Net			lb (kg)	66 (30)
		Gross				82 (37)
Outdoor Dimensions (H × W × D)		Net			in (mm)	24-7/8 × 31-7/16 × 11-7/16 (632 × 799 × 290)
		Gross				27-1/4 × 37 × 14-3/4 (692 × 940 × 375)
Outdoor Weight		Net			lb (kg)	84 (38)
		Gross				93 (42)
Indoor Fan	Airflow rate	Cooling	High	CFM (m³/h)	500 (850)	
			Med		400 (680)	
			Low		347 (590)	
			Quiet		300 (510)	
		Heating	High		500 (850)	
			Med		400 (680)	
			Low		347 (590)	
			Quiet		300 (510)	
	Type × Qty					SIROCCO FAN × 1
	Motor output			W		154
Static pressure range					inWG (Pa)	0.12 to 0.80 (30 to 200)
Outdoor Fan	Airflow rate	Cooling			CFM (m³/h)	1,171 (1,990)
		Heating				1,089 (1,850)
	Type × Qty					PROPELLER FAN × 1
	Motor output			W		49
Indoor Sound Pressure Level ¹⁴		Cooling	High	dB (A)	35	
			Med		30	
			Low		27	
			Quiet		24	
		Heating	High		35	
			Med		30	
			Low		27	
			Quiet		24	
Outdoor Sound Pressure Level ¹⁴		Cooling			48	
		Heating			49	

SUBMITTAL - 12KUAS1R

SPECIFICATIONS:

Outdoor Refrigerant		Type		R32	
		Charge	lb oz	2 lb 4 oz	
			g	1020	
Additional Charge Calculation			oz/ft	0.22	
			g/m	20	
Outdoor Refrigerant Oil		Type		RMM68AF	
		Amount	in ³ (cm ³)	24.4 (400)	
Indoor Moisture removal			pints/h (L/h)	1.5 (0.7)	
Indoor Drain hose		Material		POLYVINYL CHLORIDE	
		Tip Diameter	in (mm)	I.D.: Ø13/16 (Ø20.7), O.D.: Ø1-1/16 (Ø26.6)	
Indoor Operation range		Cooling	°F (°C)	64 to 90 (18 to 32)	
		Heating	%RH	80 or less	
			°F (°C)	60 to 86 (16 to 30)	
Power Supply				208/230 V~ 60 Hz	
Available Voltage Range				187—253	
System power supply		Voltage		208/230	
		Frequency		60	
		Available voltage range		187—253	
Indoor Current	Cooling		A	4.2	
	Heating			5.5	
Maximum Operating Current* ³		Cooling		10.2	
		Heating		11.7	
Outdoor Starting Current				5.5	
MCA* ⁵				11.7	
Wiring spec.* ⁶		MAX. CKT. BKR* ⁷		15	
Indoor Input Power	Heating	Cooling		kW	0.94
		47°FDB (Outdoor temp.)	1.25		
		17°FDB (Outdoor temp.)* ¹	1.07		
		5°FDB (Outdoor temp.)* ²	2.12		
			2.25		
Indoor Power Factor	Cooling		%	97.3	
	Heating			98.8	
Energy Star* ⁹				ES, ESCC, ESME	

NOTES:

- Cooling: Indoor temperature of 80°F (26.67°CDB)/67°FDB (19.44°CWB), and outdoor temperature of 95°FDB (35°CDB)/75°FDB (23.9°CWB).
- Heating: Indoor temperature of 70°FDB (21.11°CDB)/60°FDB (15.56°CWB), and outdoor temperature of 47°FDB (8.33°CDB)/43°FDB (6.11°CWB).
- *1: Heating (17°F): Indoor temperature of 70°FDB (21.11°CDB)/60°FDB (15.56°CWB), and outdoor temperature of 17°FDB (-8.33°CDB)/15°FDB (-9.44°CWB).
- *2: Heating (5°F): Indoor temperature of 70°FDB (21.11°CDB)/60°FDB (15.56°CWB), and outdoor temperature of 5°FDB (-15.0°CDB)/4°FDB (-15.56°CWB).
- Test conditions are based on AHRI 210/240 2023.

- *4: Indoor Sound Pressure Level: Measured values in manufacturer's anechoic chamber.
- *5: Outdoor Sound Pressure Level: Because of the surrounding sound environment, the sound levels measured in actual installation conditions might be higher than the specified values here.
- *3:

- Maximum Operating Current – Maximum current is maximum value when operated within the operation range.
- The total current of indoor unit and outdoor unit.

MCA – *5: Minimum Circuit Ampacity (Calculation based on UL60335-2-40)

– *6: Selected sample based on Japan Electrotechnical Standards and Codes Committee E0005.

Wiring spec. As the regulations of wire size and circuit breaker differ in each country or region, select appropriate devices complied to the regional standard.

MAX. CKT. BKR – *7: Maximum Circuit Breaker

Operation Range – *8: Suction temperature of the outdoor unit.

Energy Star – *9 : ES = Energy Star, ESCC = Energy Star Cold Climate, ESME= Energy Star Most Efficient.

System continues to operate below rated outdoor operation temperature range, subject to varying conditions. System has no low temperature cut out. Capacity is not tested outside of the rated temperature range.

SUBMITTAL - 12KUAS1R

ACCESSORIES:

Model Number	Description
UTY-RVRU	KAGAMI - Touch Panel Wired Controller
UTY-RNRUZ5	Touch Panel Wired Remote Controller
UTY-RHRY	Simple Wired Remote (Without Mode Function) - Hospitality
UTY-RSRY	Simple Wired Remote (With Mode Function)
UTY-LBTUM	IR Receiver Kit w/ Wireless Remote Controller (Mid-Static Ducted)
UTY-TFSXJ4	Wi-Fi adapter (WiFi Interface Module UART Type)
FJ-AC-WIFI-1	Intesis Wi-Fi Device: Wired Module
FJ-IR-WIFI-1NA ^{*1}	Intesis IR Wireless AC Cloud Control Interface (Intesis Home app)
BM101WA ^{*1}	Cielo - Breez Max IR Controller w/ WiFi (Black)
BM102WA ^{*1}	Cielo - Breez Max IR Controller w/ WiFi (White)
UTY-VMSX	Modbus Converter
UTY-VTGX	Network Converter - Convert H-Series Comm. Protocol to V/J-Series Comm.
FJ-AC-485-1	Intesis - BACnet MSTP & Modbus RTU Gateway
UTY-TERX	External Switch Controller
UTY-TTRXZ1 ^{*2}	24V Thermostat Interface
TTRXZ1-KIT ^{*2}	24V Thermostat Interface Kit (UTY-TTRXZ1, UTY-WIFI Plug & 24V Transformer)
UTY-XSZXZ1	Remote Temperature Sensor
UTY-XCSX	External input and output PCB
UTY-XWZXZG	External Connect Kit
UTZ-GXNA	External input and output PCB Bracket
UTD-LFNC	Long Life Filter (12k units)
UTY-DSGYZ2 ^{*3}	Airstage Edge Controller
UTZ-DUHGG2A	Hail Guard
UTZ-DUSHG2A	Snowhood
UTZ-DUWBG2A	Wind Baffle

NOTES:

*1 -Requires IR receiver kit UTY-LBTUM to connect this device to IDU.


*2 -This device may not be used with any other type of controls (central controller, wire/wireless RC, WiFi adapter, BMS interface).

*3 -Connection to AIRSTAGE Cloud requires a compatible AIRSTAGE Mobile adapter connected to the IDU.

SUBMITTAL - 12KUAS1R

INDOOR UNIT DIMENSIONS:

Unit: in (mm)



SUBMITTAL - 12KUAS1R

OUTDOOR UNIT DIMENSIONS:

Unit: in (mm)

