

PAA-CA36NL & SUZ-AK36NLHZ  
32,000 BTU/H CASD COIL INDOOR UNIT  
36,000 BTU/H HYPER HEAT PUMP OUTDOOR UNIT



Job Name:

System Reference:

Date:



INDOOR Unit ... PAA-CA36NL

OUTDOOR Unit ... SUZ-AK36NLHZ

#### INDOOR UNIT FEATURES

- **Furnace Compatible:** Compatible with most gas furnaces, intelli-HEAT® allows for Intelligent Switchover between the furnace and heat pump operation.  
\*Mitsubishi Electric air-conditioner and heat pump systems should only be connected with ANSI-Z21.47/CSA2.3 certified furnaces
- **Intelligent Switchover:** Intelligent Switchover from electric heat pump to gas furnace operation in extreme cold for consistent comfort. The system can also be set to switch based optimal energy efficiency and to reduce your carbon footprint.
- **High Quality Drain Pan:** High quality drain pan material with high heat tolerance and low moisture absorption
- **Multi-Position Installation:** Versatile installation options, including horizontal (left or right) and vertical (up or down) orientations, with included drain pans to facilitate easy setup for any configuration.
- **Available Widths:** Available in 14.5", 17.5", and 21" widths

#### OUTDOOR UNIT FEATURES

- **H2i® Hyper-Heating:** 100% heating performance down to 5° F with guaranteed heating down to -13° F.
- **Inverter Driven Compressor:** Inverter technology uses only the precise amount of energy needed to keep a space comfortable.
- **Blue Fin Coating:** Anti-corrosion coating that protects the outdoor heat exchanger against salt, sulfur, and other airborne contaminants that impact the efficiency and performance of the outdoor units.
- **Base Pan Heater:** This advanced base pan heater helps to prevent interrupted operation due to water freezing after a defrost cycle, ensuring your warmth and comfort during colder weather.
- **Seacoast Protection:** Designed to protect against the corrosive effects of environments that are in close proximity to the sea.
- **Flash Injection:** Flash Injection enables optimum compressor performance when it is running at higher speeds to maintain indoor comfort during cold temperatures.

**SPECIFICATIONS: PAA-CA36NL & SUZ-AK36NLHZ**

Cooling at 95F <sup>1</sup>	Maximum Capacity	Btu/h	36000
	Rated Capacity	Btu/h	32000
	Minimum Capacity	Btu/h	16200
	Maximum Power Input	W	3200
	Rated Power Input	W	2720
	Moisture Removal	Pints/h	6.80
	Sensible Heat Factor		0.78
Heating at 47F <sup>2</sup>	Power Factor [208V / 230V]	%	87 / 87
	Maximum Capacity	Btu/h	42000
	Rated Capacity	Btu/h	42000
	Minimum Capacity	Btu/h	19200
	Maximum Power Input	W	3500
	Rated Power Input	W	3500
Heating at 17F <sup>3</sup>	Power Factor [208V / 230V]	%	90 / 90
	Maximum Capacity	Btu/h	38000
	Rated Capacity	Btu/h	31200
	Maximum Power Input	W	6220
	Rated Power Input	W	3810
Heating at 5F <sup>5</sup>	Maximum Capacity	Btu/h	38000
Heating at -13F <sup>9</sup>	Maximum Power Input	W	5860
	Maximum Capacity	Btu/h	28400
Efficiency	SEER2		17.20
	EER2 <sup>1</sup>		11.70
	HSPF2 [I/V]		8.90
	COP at 47°F <sup>2</sup>		3.5
	COP at 17°F at Maximum Capacity <sup>3</sup>		1.70
	COP at 5°F at Maximum Capacity <sup>5</sup>		1.90
	COP at -13°F at Maximum Capacity <sup>9</sup>		1.82
ENERGY STAR® Certified		Yes	
Electrical	Voltage, Phase, Frequency	V AC / V AC , Hz	208 / 230 , 1 , 60
	Guaranteed Voltage Range	V AC	198 - 253
	Voltage: Indoor - Outdoor, S1-S2	V AC	208/230
	Voltage: Indoor - Outdoor, S2-S3	V DC	12-24
	Short-circuit Current Rating [SCCR]	kA	5
	Recommended Fuse/Breaker Size (Outdoor)	A	30
Indoor Unit	Recommended Wire Size [Indoor - Outdoor]	AWG	14
	MCA	A	0.2
	Rated Airflow, Dry	CFM	1050
	Maximum Airflow, Dry	CFM	1201
	Minimum Airflow, Dry	CFM	800
	Internal Static Pressure [at Rated CFM]	in.WG	0.2
	Drain Pipe Size O.D.	inch [ mm ]	3/4 [ 19.05 ]
	Unit Dimensions (W x D x H)	inch x inch x inch [ mm x mm x mm ]	21-1/8 x 21-7/16 x 32 [ 535 x 543 x 812 ]
	Package Dimensions (W x D x H)	inch x inch x inch [ mm x mm x mm ]	22-14/16 x 25-5/16 x 37-8/16 [ 580 x 695 x 953 ]
	Unit Weight [Cased Coil Only]	lbs [ kg ]	79.4 [ 36.0 ]
	Control Box Weight	lbs [ kg ]	5.1 [ 2.3 ]
Package Weight	lbs [ kg ]	105.8 [ 48.0 ]	
IDU Operating Temp. Range	Cooling Intake Air Temp [Maximum / Minimum]	deg F , deg F / deg F , deg F	90 , 73 / 66 , 59
	Heating Intake Air Temp [Maximum / Minimum]	deg F	83 / 50
Outdoor Unit	MCA	A	29
	MOCP	A	48
	Fan Motor Output	W	74+74
	Airflow Rate Cooling	CFM	3740
	Airflow Rate Heating	CFM	3740
	Defrost Method		Reverse Cycle
<b>Notes</b>			

**SPECIFICATIONS: PAA-CA36NL & SUZ-AK36NLHZ**

Outdoor Unit	Coating on Heat Exchanger (Bluefin, Sea Coast)		Yes , Yes
	Sound Pressure Level, Cooling <sup>1</sup>	dB (A)	52
	Sound Pressure Level, Heating <sup>2</sup>	dB (A)	53
	Compressor Type		Twin Rotary
	Compressor Model		MRK36FFGMC
	Compressor Oil [Type // Charge]	// oz	RM68EH // 45
	External Finish Color		Munsell No.3Y 7.8/1.1
	Base Pan Heater		Built-in
	Unit Dimensions (W x D x H)	inch x inch x inch [ mm x mm x mm ]	41-11/32 x 14 x 52-43/64 [ 1050 x 355 x 1338 ]
	Package Dimensions (W x D x H)	inch x inch x inch [ mm x mm x mm ]	42-15/16 x 17-3/4 x 58-5/16 [ 1090 x 450 x 1480 ]
	Unit Weight	lbs [ kg ]	231 [ 105 ]
	Package Weight	lbs [ kg ]	258 [ 117 ]
	ODU Operating Temp. Range	Cooling Intake Air Temp [Maximum / Minimum*]	F
Heating Intake Air Temp [Maximum / Minimum]		F , F / F , F	70 , 59 / -13 , -13
Heating Thermal Lock-out / Re-start Temperatures**		F	-22 / -13
Refrigerant	Type		R454B
	Pre-Charged Refrigerant Amount	lbs , oz	9 , 14
	Maximum Pre-Charged Piping Length	ft [ m ]	100 [ 30 ]
	Additional Refrigerant Charge Per Additional Piping Length	oz/ft	0.6
Piping	Gas Pipe Size O.D. [Flared]	inch [ mm ]	5/8 [ 15.88 ]
	Liquid Pipe Size O.D. [Flared]	inch [ mm ]	3/8 [ 9.52 ]
	Maximum Piping Length	ft [ m ]	100 [ 30 ]
	Maximum Height Difference	ft [ m ]	100 [ 30 ]
	Maximum Number of Bends		15
<b>Notes</b>			

## INDOOR UNIT ACCESSORIES: PAA-CA36NL

Condensate	Blue Diamond Sensor Extension Cable 15 Ft	<input type="checkbox"/> C13-103
	Blue Diamond Advanced Mini Condensate Pump w Reservoir Sensor 208230V recommended	<input type="checkbox"/> X88-721
	Refco Condensate Pump 100-240V up to 120k BTU/h	<input type="checkbox"/> COMBI
	Blue Diamond (MaxiBlue Advanced) Mini Condensate Pump w/ Reservoir & Sensor (110V) up to 48,000 BTU/H [recommended]	<input type="checkbox"/> X87-711
	Blue Diamond MegaBlue Condensate Pump with Reservoir Sensor 115-230V up to 170k BTU/h	<input type="checkbox"/> X87-835
	Sauermann Condensate Pump 120-230V up to 60k BTU/h	<input type="checkbox"/> SI30-230
Control Interface	Wireless Interface 2 for Comfrot app	<input type="checkbox"/> PAC-USWHS002-WF-2
	kumo station® for Comfort app	<input type="checkbox"/> PAC-WHS01HC-E
	IT Extender	<input type="checkbox"/> PAC-WHS01IE-E
	Operation and Error Status Output Adapter <sup>1</sup></sup>	<input type="checkbox"/> PAC-SF40RM-E
	Procon BACnet® and Modbus® Interface	<input type="checkbox"/> PAC-UKPRC001-CN-1
	Thermostat Interface	<input type="checkbox"/> PAC-US446CN-1
Disconnect Switch	(30A/600V/UL) [fits 2" X 4" utility box] - White	<input type="checkbox"/> TAZ-MS303W
	30A600VUL fits 2 X 4 utility box - Black	<input type="checkbox"/> TAZ-MS303
Lineset	3/8 x 5/8 Lineset Twin-Tube Insulation - 50 feet	<input type="checkbox"/> MPLS385812T-50
	3/8 x 5/8 Lineset Twin-Tube Insulation - 10 feet	<input type="checkbox"/> MPLS385812T-10
	3/8 x 5/8 Lineset Twin-Tube Insulation - 15 feet	<input type="checkbox"/> MPLS385812T-15
	3/8 x 5/8 Lineset Twin-Tube Insulation - 30 feet	<input type="checkbox"/> MPLS385812T-30
	3/8 x 5/8 Lineset Twin-Tube Insulation - 65 feet	<input type="checkbox"/> MPLS385812T-65
	3/8 x 5/8 Lineset Twin-Tube Insulation - 100 feet	<input type="checkbox"/> MPLS385812T-100
Power Supplies & Auxiliary Components	ERV On/Off Input Adapter for CNER on SVZ PEAD and PVA models	<input type="checkbox"/> PAC-740
Remote Sensor	Flush Mount Remote Temperature Sensor for SEZ SLZ SVZ and all P-Series models	<input type="checkbox"/> PAC-USSEN002-FM-1
	Wall Mounted Remote Temperature Sensor	<input type="checkbox"/> PAC-SE41TS-E
	Wireless temperature and humidity sensor for Comfort app	<input type="checkbox"/> PAC-USWHS003-TH-1
Terminal Signal Adapter	3-Pin Wiring Harness	<input type="checkbox"/> PAC-715AD
	5-Pin Wiring Harness	<input type="checkbox"/> PAC-725AD
	Backup Heat Relay Kit	<input type="checkbox"/> CN24RELAY-KIT-CM3
Wired Remote Controller	Deluxe MA Wired Remote Controller	<input type="checkbox"/> PAR-42MAAUB
	Touch MA Remote Controller	<input type="checkbox"/> PAR-CT01MAU-SB
	Simple MA Remote Controller	<input type="checkbox"/> PAC-YT53CRAU-J
	Simple Direct Wired Remote Controller	<input type="checkbox"/> PAC-SDW01RC-1
Wireless Remote Controller	Universal Wireless Receiver for PAR-FL32MA-E	<input type="checkbox"/> PAR-FA32MA-W
	Wireless RedLINK™ Remote Controller	<input type="checkbox"/> MHK2
	Universal Wireless Receiver for PAR-FL32MA-E	<input type="checkbox"/> PAR-FA32MA-E
	Lockdown Bracket for Wireless Handheld Remote Controllers	<input type="checkbox"/> RCMKP1CB
	Wireless Remote Controller	<input type="checkbox"/> PAR-SL101A-E
<b>Notes</b>		

## OUTDOOR UNIT ACCESSORIES: SUZ-AK36NLHZ

Air Outlet Guide	Air Outlet Guide 1 Piece	<input type="checkbox"/>	PAC-SH96SG-E (two pieces required)
Centralized Drain Pan	Centralized Drain Pan	<input type="checkbox"/>	PAC-SH97DP-E
Control/Service Tool	USB Conversion Cable for PAC-USCMS-MN-1	<input type="checkbox"/>	M21EC1397
	Maintenance Tool Interface	<input type="checkbox"/>	PAC-USCMS-MN-1
	ControlService Tool	<input type="checkbox"/>	PAC-SK52ST
	M- & P-Series Maintenance Tool Cable Set	<input type="checkbox"/>	M21EC0397
Drain Socket	Drain Socket	<input type="checkbox"/>	PAC-SG61DS-E
Hail Guards	Hail Guard	<input type="checkbox"/>	HG-A2
M-NET Converter	M-Net Interface for P-Series	<input type="checkbox"/>	PAC-SJ95MA-E
Mini-Split Wire	14 Gauge 4 wire Armored MiniSplit Cable50 ft roll	<input type="checkbox"/>	SW144-50
	16 Gauge 4 wire MiniSplit Cable250 ft roll	<input type="checkbox"/>	S164-250
	14 Gauge 4 wire MiniSplit Cable50 ft roll	<input type="checkbox"/>	S144-50
	14 Gauge 4 wire Armored MiniSplit Cable250 ft roll	<input type="checkbox"/>	SW144-250
	16 Gauge 4 wire MiniSplit Cable50 ft roll	<input type="checkbox"/>	S164-50
	14 Gauge 4 wire MiniSplit Cable250 ft roll	<input type="checkbox"/>	S144-250
Mounting Pad	Condensing Unit Mounting Pad 24 x 42 x 3	<input type="checkbox"/>	ULTRILITE2
Snow/Rain Diverter	SnowRain Diverter	<input type="checkbox"/>	SRD-5
Stand	24 Dual Fan Stand	<input type="checkbox"/>	QSMS2402M
	Outdoor Unit 3-14 inch Mounting Base Pair - Plastic	<input type="checkbox"/>	DSD-400P
	Outdoor Unit Stand 12 High	<input type="checkbox"/>	QSMS1202M
	18 Dual Fan Stand	<input type="checkbox"/>	QSMS1802M
Terminal Signal Adapter	5-Pin Wiring Harness	<input type="checkbox"/>	PAC-725AD
	3-Pin Wiring Harness	<input type="checkbox"/>	PAC-715AD
Wind Baffle	Front Wind Baffle	<input type="checkbox"/>	WB-PA3 (two pieces required)
<b>Notes</b>			

# INDOOR UNIT DIMENSIONS: PAA-CA36NL



