

PLA-AE36NL & PUZ-AK36NL
36,000 BTU/H CEILING CASSETTE INDOOR UNIT
36,000 BTU/H HEAT PUMP OUTDOOR UNIT



Job Name:

System Reference:

Date:



Indoor Unit.....PLA-AE36NL

Outdoor Unit.....PUZ-AK36NL



INDOOR UNIT FEATURES

- 3D i-see Sensor®: The advanced sensor scans each room to produce a complete thermal profile that includes heat signatures based upon size, temperature and movement, then adjusts temperature and airflow based on user preference, and saves energy according to room occupancy.
- Available Knockouts: Knockouts for outside-air intake and branch-duct run
- Built-in condensate lift mechanism
- Easy-to-clean filter: Easy-to-clean, washable filter (optional high-efficiency filter available - requires multi-function casement)
- Filter indicator signal
- Ideal PLA spaces: Ideal for retail shops, classrooms, office spaces, conference centers, building lobbies, and more
- Individual vane settings: Individual vane settings for direct/indirect airflow control or variable airflow patterns
- Light commercial: Units with this icon are suitable for light commercial applications such as small offices, restaurants, and retail.
- Multiple control options, including the comfort app for remote access, third-party interfaces, and both wired and wireless controllers
- PLA Airflow settings: Airflow settings for high and low ceiling applications
- Space-efficient ductless installation
- Up and down swing-mode: An indoor unit with this capability can move air up and down throughout the room like an oscillating fan using the horizontal vanes.

OUTDOOR UNIT FEATURES

- High pressure/temperature protection
- High speed heating at start up: High speed heating at start up: Hyper-Heating INVERTER® reduces the time for heating at start up by about half compared to standard models

SPECIFICATIONS: PLA-AE36NL & PUZ-AK36NL

Cooling at 95F ¹	Maximum Capacity	Btu/h	36,600
	Rated Capacity	Btu/h	36,000
	Minimum Capacity	Btu/h	14,300
	Maximum Power Input	W	2,740
	Rated Power Input	W	2,620
	Moisture Removal	Pints/h	8
	Sensible Heat Factor	-	0.76
Heating at 47F ²	Power Factor [208V / 230V]	%	97 / 97
	Maximum Capacity	Btu/h	40,000
	Rated Capacity	Btu/h	40,000
	Minimum Capacity	Btu/h	13,000
	Maximum Power Input	W	2,570
	Rated Power Input	W	2,570
	Power Factor [208V / 230V]	%	97 / 97
Heating at 17F ³	Maximum Capacity	Btu/h	23,600
	Rated Capacity	Btu/h	23,600
	Maximum Power Input	W	2,230
	Rated Power Input	W	2,230
Heating at 5F ⁴	Maximum Capacity	Btu/h	20,000
	Maximum Power Input	W	2,100
Heating at -4F ⁵	Maximum Capacity	Btu/h	17,600
Efficiency	SEER2		23.3
	EER2 ¹		13.7
	HSPF2 [IV]		9.8
	COP at 47°F ²		4.5
	COP at 17°F at Maximum Capacity ³		3.1
	COP at 5°F at Maximum Capacity ⁴		2.7
	COP at -4°F at Maximum Capacity ⁵		2.58
Electrical	ENERGY STAR® Certified		Yes
	Voltage, Phase, Frequency	V AC / V AC, , Hz	208 / 230, 1, 60
	Guaranteed Voltage Range	V AC	198 - 264
	Voltage: Indoor - Outdoor, S1-S2	V AC	208/230
	Voltage: Indoor - Outdoor, S2-S3	V DC	28
	Short-circuit Current Rating [SCCR]	kA	5
	Recommended Fuse/Breaker Size (Outdoor)	A	35
Indoor Unit	Recommended Wire Size [Indoor - Outdoor]	AWG	14
	Fan Motor Output	W	120
	Airflow Rate at Cooling, Dry	CFM	670, 850, 1,020, 1,200
	Airflow Rate at Heating, Dry	CFM	670, 850, 1,020, 1,200
	Sound Pressure Level [Cooling]	dB (A)	32, 37, 41, 44
	Sound Pressure Level [Heating]	dB (A)	32, 37, 41, 44
	External Finish Color		1.0Y 9.2/0.2
	Unit Dimensions (W x D x H)	inch x inch x inch [mm x mm x mm]	33-1/16 x 33-1/16 x 11/3/2004 [840 x 840 x 298]
	Package Dimensions (W x D x H)	inch x inch x inch [mm x mm x mm]	34-5/16 x 35-9/16 x 15 [871 x 903 x 381]
	Unit Weight	lbs [kg]	57 [26]
	Package Weight	lbs [kg]	82 [37]
	Fan Motor Type		DC Motor
IDU Operating Temp. Range	Cooling Intake Air Temp [Maximum / Minimum]	°FDB, °FWB / °FDB, °FWB	90, 73 / 66, 59
	Heating Intake Air Temp [Maximum / Minimum]	°FDB	82 / 50

NOTES

¹Cooling at 95°F (Indoor: 80°F DB, 67°F WB // Outdoor: 95°F DB, 75°F WB)

²Heating at 47°F (Indoor: 70°F DB, 60°F WB // Outdoor: 47°F DB, 43°F WB)

³Heating at 17°F (Indoor: 70°F DB, 60°F WB // Outdoor: 17°F DB, 15°F WB)

⁴Heating at 5°F (Indoor: 70°F DB, 60°F WB // Outdoor: 5°F DB, 4°F WB)

⁵Heating at -4°F (Indoor: 70°F DB, 60°F WB // Outdoor: -4°F DB, -5°F WB)

*Indoor/Outdoor Unit Operating Temperature Range (Cooling Air Temp [Maximum / Minimum]):

• Wind baffles required to operate below 23°F DB in cooling mode.

• Heat pump system with wind baffle: 0°F - 115°F.

• Refer to wind baffle documentation for further information.

** Outdoor Unit Operating Temperature Range (Cooling Thermal Lock-out / Re-start Temperatures; Heating Thermal Lock-out / Re-start Temperatures):

• System cuts out in heating mode and automatically restarts at these temperatures.

SPECIFICATIONS: PLA-AE36NL & PUZ-AK36NL

Outdoor Unit	MCA	A	34
	MOCP	A	56
	Fan Motor Output	W	74
	Airflow Rate Cooling	CFM	3,910
	Airflow Rate Heating	CFM	3,910
	Defrost Method		Reverse Cycle
	Coating on Heat Exchanger (Bluefin, Sea Coast)		Yes, Yes
	Sound Pressure Level, Cooling ¹	dB (A)	52
	Sound Pressure Level, Heating ²	dB (A)	53
	Compressor Type		Twin Rotary
	Compressor Model		MRB36FEGMC
	Compressor Oil [Type // Charge]	Type // oz	RM68EH // 45
	External Finish Color		Munsell No.3Y 7.8/1.1
	Base Pan Heater		Optional
	Unit Dimensions (W x D x H)	inch x inch x inch [mm x mm x mm]	41-11/32 x 13-31/32 x 52-43/64 [1,050 x 355 x 1,338]
	Package Dimensions (W x D x H)	inch x inch x inch [mm x mm x mm]	42-15/16 x 17-3/4 x 58-5/16 [1,090 x 450 x 1,480]
ODU Operating Temp. Range	Unit Weight	lbs [kg]	224 [102]
	Package Weight	lbs [kg]	251.33 [114]
	Cooling Intake Maximum Air Temp [Maximum / Minimum*]	°FDB	115 / 23
	Heating Air Temp [Maximum / Minimum]	°FDB, °FWB / °FDB, °FWB	70, 59 / -4, -4
Refrigerant	Heating Thermal Lock-out / Re-start Temperatures**	°FDB	-13 / -4
	Type		R454B
	Pre-Charged Refrigerant Amount	lbs, oz	9, 14
	Maximum Pre-Charged Piping Length	ft [m]	100 [30]
	Additional Refrigerant Charge Per Additional Piping Length	oz/ft	0.6
Piping	Gas Pipe Size O.D. [Flared]	inch [mm]	8-May [15.88]
	Liquid Pipe Size O.D. [Flared]	inch [mm]	8-Mar [9.52]
	Maximum Piping Length	ft [m]	165 [50]
	Maximum Height Difference	ft [m]	100 [30]
	Maximum Number of Bends		15

NOTES

¹Cooling at 95°F (Indoor: 80°F DB, 67°F WB // Outdoor: 95°F DB, 75°F WB)

²Heating at 47°F (Indoor: 70°F DB, 60°F WB // Outdoor: 47°F DB, 43°F WB)

³Heating at 17°F (Indoor: 70°F DB, 60°F WB // Outdoor: 17°F DB, 15°F WB)

⁴Heating at 5°F (Indoor: 70°F DB, 60°F WB // Outdoor: 5°F DB, 4°F WB)

⁵Heating at -4°F (Indoor: 70°F DB, 60°F WB // Outdoor: -4°F DB, -5°F WB)

*Indoor/Outdoor Unit Operating Temperature Range (Cooling Air Temp [Maximum / Minimum]):

• Wind baffles required to operate below 23°F DB in cooling mode.

• Heat pump system with wind baffle: 0°F - 115°F.

• Refer to wind baffle documentation for further information.

** Outdoor Unit Operating Temperature Range (Cooling Thermal Lock-out / Re-start Temperatures; Heating Thermal Lock-out / Re-start Temperatures):

• System cuts out in heating mode and automatically restarts at these temperatures.

INDOOR UNIT ACCESSORIES: PLA-AE36NL






Lineset	10 x 3/8 x 10 x 5/8 Lineset Twin-Tube Insulation	MPLS385812T-10
	100 x 3/8 x 100 x 5/8 Lineset Twin-Tube Insulation	MPLS385812T-100
	15 x 3/8 x 15 x 5/8 Lineset Twin-Tube Insulation	MPLS385812T-15
	30 x 3/8 x 30 x 5/8 Lineset Twin-Tube Insulation	MPLS385812T-30
	50 x 3/8 x 50 x 5/8 Lineset Twin-Tube Insulation	MPLS385812T-50
	65 x 3/8 x 65 x 5/8 Lineset Twin-Tube Insulation	MPLS385812T-65
Shutter Plate	Shutter Plate	PAC-SJ37SP-E
Wired Remote Controller	Deluxe Wired MA Remote Controller ¹	PAR-42MAAUB
	Simple Direct Wired Remote Controller	PAC-SDW01RC-1
	Simple MA Remote Controller ¹	PAC-YT53CRAU-J
	Touch MA Wired Remote Controller ¹	PAR-CT01MAU-SB
i-see Sensor® Panel	Grille with 3D i-see Sensor (required)	PLP-41EAEU
Disconnect Switch	30A600VUL fits 2 X 4 utility box - Black	TAZ-MS303
	30A600VUL fits 2 X 4 utility box - White	TAZ-MS303W
Wireless Remote Controller	Lockdown Bracket for Wireless Handheld Remote Controllers	RCMKP1CB
	RedLINK Wireless Remote Controller	MHK2
	Universal Wireless MA Handheld Remote Controller	PAR-FL32MA-E
	Universal Wireless Receiver for PAR-FL32MA-E	PAR-FA32MA-W
	Wireless Handheld Remote Controller for SLZ PLA and PLFY models	PAR-SL101A-E
	Wireless Receiver for PAR-SL101A-E on PLA-NL and PLFY-ELNEMU models	PAR-SR4LU-E
	Wireless Remote Receiver Panel	PAR-SR3LA-E
Power Supplies & Auxiliary Components	3-Pin Wiring Harness	PAC-715AD
	5-Pin Wiring Harness	PAC-725AD
Control Interface	Airzone Wired Blueface Controller Black	AZZBSBLUEZEROCN
	Airzone Wired Blueface Controller White	AZZBSBLUEZEROCB
	Airzone Wireless Lite Controller Black	AZZBSLITERN
	Airzone Wireless Lite Controller White	AZZBSLITERB
	Airzone Wireless Think Controller Black	AZZBSTHINKRN
	Airzone Wireless Think Controller White	AZZBSTHINKRB
	IT Extender for kumo station	PAC-WHS01IE-E
	kumo station for the Comfort app	PAC-WHS01HC-E
	Operation and Error Status Output Adapter ¹	PAC-SF40RM-E
	Procon BACnet and Modbus Interface	PAC-UKPRC001-CN-1
	Thermostat Interface for 3rd Party Thermostats	PAC-US445CN-1
	Wireless Interface Adapter for the Comfort app	PAC-USWHS002-WF-2
Space Panel	Space Panel	PAC-SJ38AS-E
Power Supplies and Auxiliary Components	Backup Heat Relay Kit Adapter for CN24 or CN152 Connector	CN24RELAY-KIT-CM3
Condensate	Blue Diamond Advanced Mini Condensate Pump w Reservoir Sensor 208230V recommended	X87-721
	Blue Diamond MaxiBlue Advanced Mini Condensate Pump w Reservoir Sensor 110V up to 48000 BTUH recommended	X87-711
	Blue Diamond MegaBlue Advanced Condensate Pump w Reservoir Sensor	X87-835
	Blue Diamond Sensor Extension Cable 15 Ft	C13-103
	Refco Condensate Pump 100-240 VAC up to 120000 BTUH	COMBI
	Sauermann Condensate Pump	SI30-230
Remote Sensor	Flush Mount Remote Temperature Sensor for SEZ SLZ SVZ and all P-Series models	PAC-USSEN002-FM-1
	Wall Mount Remote Temperature Sensor	PAC-SE41TS-E
	Wireless temperature and humidity sensor for the Comfort app	PAC-USWHS003-TH-1
Casement	Multi-function Casement	PAC-SJ41TM-E
Filter	High Efficiency Filter Element	PAC-SH59KF-E
NOTES ¹ Unable to use with Wireless Remote Controller		

OUTDOOR UNIT ACCESSORIES: PUZ-AK36NL

Control/Service Tool	ControlService Tool	PAC-SK52ST
	M- & P-Series Maintenance Tool Cable Set	M21EC0397
	Maintenance Tool Interface	PAC-USCMS-MN-1
Mounting Pad	Condensing Unit Mounting Pad 24 x 42 x 3	ULTRILITE2
Mini-Split Wire	14 Gauge 4 wire Armored MiniSplit Cable250 ft roll	SW144-250
	14 Gauge 4 wire Armored MiniSplit Cable50 ft roll	SW144-50
	14 Gauge 4 wire MiniSplit Cable250 ft roll	S144-250
	14 Gauge 4 wire MiniSplit Cable50 ft roll	S144-50
Stand	18 Dual Fan Stand	QSMS1802M
	24 Dual Fan Stand	QSMS2402M
	Condenser Wall Bracket	QSWB2000M-1
	Condenser Wall Bracket - Stainless Steel Finish	QSWBSS
	Outdoor Unit 3-14 inch Mounting Base Pair - Plastic	DSD-400P
	Outdoor Unit Stand 12 High	QSMS1202M
Power Supplies & Auxiliary Components	3-Pin Wiring Harness	PAC-715AD
	5-Pin Wiring Harness	PAC-725AD
Wind Baffle	Front Wind Baffle	WB-PA3 (two pieces are required)
	Rear Wind Baffle	WB-RE6
	Side Advanced Wind Baffle	WB-SD6
Drain Socket	Drain Socket	PAC-SG61DS-E
M-NET Converter	M-Net Interface for P-Series	PAC-SJ95MA-E
Centralized Drain Pan	Centralized Drain Pan	PAC-SH97DP-E
Snow/Rain Diverter	SnowRain Diverter	SRD-5
Air Outlet Guide	Air Outlet Guide 1 Piece	PAC-SH96SG-E (two pieces are required)
Optional Defrost Heater	Optional Defrost Heater	PAC-SL11BH-E
NOTES		

INDOOR UNIT DIMENSIONS: PLA-AE36NL

NOTE: PLEASE CHECK THE GRILLE ABOVE THE DESIGNATED GRILLES.
PREVENT THE SUSPENSION BELT OR INSUFFICIENT RESISTANCE SUPPORTING MATERIAL, WHICH
LEADING TO SWING PREVENTION IN ACCORDANCE WITH THE NECESSITY OF EARTHQUAKE
RESISTANCE. ESPECIALLY IN THE CASE WITHOUT CEILING MATERIAL, DOWN OR HORIZONTAL
DAS FOR SUSPENSION BELT, PLEASE USE MET OR WIRE PROVIDED AT LOCAL SITE.
DAS FOR BRAN PIPE, PLEASE USE V-POSSIBLE WIRE (V-PVC) TYPE.
DRAIN PUMP INCLUSION WARE IS MAX. HEIGHT 500mm FROM THE CEILING.
ELECTRICAL WIRE MAY BE POWERED FOR THE SERVICE APPROVED.
MAKE SURE TO SLACK THE ELECTRICAL WIRE LITTLE BIT FOR
CONVENTION POWER WIRE CONNECTION.
4.5mm HEIGHT OF THE INDOOR UNIT IS ABLE TO BE ADJUSTED
WITH THE GRILLE ATTACHED.
WHEN INSTALLING THE BRAN DUCTS, BE SURE TO INSULATE ADEQUATELY
TO PREVENT CONDENSATION AND DROPPING ANY DRAIN.
IF BEYOND THE CASE OF DRAIN DROPS/WATER DRAIN
RACE FOR MEDICATED INSTALLATION(SERVICE SPACE), PLEASE REFER TO THE RIGHT AT FIGURE
TYPICAL DAS REFER TO EXCLUSIVE OUTLINE DATA AND INSTALLATION INSTRUCTION
CONNECTION AND OPTION DATA PERFORMANCE IS TO BE OR SET TOTAL 15.5m UNIT




PLA-AE36NL 02/08/2014/03/06/00/148

CAPACITY OF EACH MODEL AS FOLLOWING

PLA-AE36NL	①	A	B	C	D	E	F
12-18	REFrigerant Pipe (mm)	REFrigerant Pipe (mm)	24	250	76	765	2000-7700/2000-7500
24-48	REFrigerant Pipe (mm)	REFrigerant Pipe (mm)	24	250	76	765	2000-7700/2000-7500
24-48	REFrigerant Pipe (mm)	REFrigerant Pipe (mm)	24	250	76	765	2000-7700/2000-7500

OUTDOOR UNIT DIMENSIONS: PUZ-AK36NL



1340 Satellite Boulevard Suwanee, GA 30024
Toll Free: 800-433-4822 <https://mitsubishicomfort.com>



METUS_2025-02_PROPIN

Specifications are subject to change without notice.

© 2025 Mitsubishi Electric Trane HVAC US LLC. All rights reserved.