



Submittal Data Sheet

R-32 --- 0.75 Ton, Heatpump, Ductless, ODU Daikin OTERRA
RXF09AXVJU

FEATURES

- Inverter Technology
- Swing Compressor
- Auto Restart (after power failure)
- Self Diagnosis
- Anti-Corrosion Treatment of Outdoor Heat Exchanger
- Quiet Operations

BENEFITS

- Energy Savings
- Worry Free Operations
- Long life of equipment
- R-32 Easy, Prove, Efficient, Available

INDOOR UNIT



OUTDOOR UNIT





Submittal Data Sheet

R-32 --- 0.75 Ton, Heatpump, Ductless, ODU Daikin OTERRA
RXF09AXVJU

EFFICIENCY:	
COOLING:	HEATING:
SEER	HSPF
EER	COP

PERFORMANCE:			
COOLING (Btu/Hr):		HEATING (Btu/Hr):	
Rated:(Min/Max):	9,000 (4,400 / 11,200)	47° Rated:(Min/Max):	10,000 (/)
Sensible AHRI:		17° Rated:	Add MSS
Moisture Removal (Gal/Hr):	0.1	5° Max:	Add MSS
Standard Operating Range:	50°F - 118°F	Operating Range:	5°F - 64°F
Extended Operating Range:	°F - °F	47° Rated Heating Conditions:	Indoor (°F DB/WB): 70 / 60 Ambient (°F DB/WB): 47 / 43
Rated Cooling Conditions:	Indoor (°F DB/DB): 80 / 67 Ambient (°F DB/WB): 95 / 75	17° Rated Heating Conditions:	Indoor (°F DB/WB): 70 / 60 Ambient (°F DB/WB): 47 / 43

ELECTRICAL			PIPING	
Power Supply (V/Hz/Ph): *See Engineering Manuals for other voltages.			*208-230 / 60 / 1	Gas Connection (in): 3/8
System MCA:			9.3	Liquid Connection (in): 1/4
System MFA:			15.0	Drain Connection (in): 5/8
Compressor RLA:				Max. Interunit Piping Length (ft): 66
Outdoor fan motor FLA:			0.6	Max. Interunit Height Difference (ft): 49.25
Outdoor fan motor W:			26.0	Refrigerant Pre-Charged Pipe Length (ft): 33
Indoor fan motor FLA:				Additional Charge of Refrigerant (oz/ft): 0.18
Indoor fan motor W:			26.0	
MCA: Min.circuit amps	MFA: Max.fuse amps	RLA: Rated load amps		
			FLA: Full load amps	W: Rated output watts


Submittal Data Sheet

R-32 --- 0.75 Ton, Heatpump, Ductless, ODU Daikin OTERRA
 RXF09AXVJU

INDOOR SPECIFICATIONS					
COOLING - Airflow Rate (cfm):			HEATING - Airflow Rate (cfm):		
High:	1,051	Med:	High:	966	Med:
Low:		SuperLow:	Low:		SuperLow:
Sound Pressure (H) (dBA):	46		Sound Pressure (H) (dBA):	48	
Dimensions (HxWxD) (in):	21-11/16 x 26-1/2 x 11-3/16		Net Weight (lb):	60	

DIMENSIONAL DRAWING - INDOOR UNIT

Model : RKF09/12A, RXF09/12A






Submittal Data Sheet

R-32 --- 0.75 Ton, Heatpump, Ductless, ODU Daikin OTERRA
RXF09AXVJU

OUTDOOR SPECIFICATIONS			
COOLING - Airflow Rate (cfm):		HEATING - Airflow Rate (cfm):	
High:	1,051	High:	966
SuperLow:		SuperLow:	
Compressor Stage:	Inverter	Refrigerant Type:	R-32
Factory Charge (Lbs):	1.65	Refrigerant Oil:	PVE (FVC50K)
Sound Pressure Level (dBA):	46		
Dimensions (HxWxD) (in):	21-11/16 x 26-1/2 x 11-3/16	Net Weight (lb):	60

DIMENSIONAL DRAWING - OUTDOOR UNIT

Model : RKF09/12A, RXF09/12A





Submittal Data Sheet

R-32 --- 0.75 Ton, Heatpump, Ductless, ODU Daikin OTERRA
RXF09AXVJU

ACCESSORIES

PART NUMBER	DESCRIPTION	INCLUDED
DACA-WB-3	Powder-Coated Wall-Mounted Bracket	No
KEH067A41E	Daikin BMS DrainPan Heater Small RX09,12 and RXN09,12	No
KKG067A41	Back protection wire net (09 & 12)	No
KPW937F4	Air direction adjustment grille (09 & 12)	No