



Submittal Data Sheet

21.0 SEER2, Heat Pump, Ductless ODU, 1.25 Ton, Daikin AURORA R-32
RXT15AVJU9

FEATURES

- Swing Inverter Compressor
- Extended Operating Range and Capacity
- Automatic Defrost

BENEFITS

- 12 Year Registered Residential Warranty
- 5 Year Commercial Warranty
- Cooling 50-115F
- Heating -13-60F

INDOOR UNIT



OUTDOOR UNIT





Submittal Data Sheet

21.0 SEER2, Heat Pump, Ductless ODU, 1.25 Ton, Daikin AURORA R-32
RXT15AVJU9

EFFICIENCY:	
COOLING:	HEATING:
SEER	HSPF
EER	COP

PERFORMANCE:			
COOLING (Btu/Hr):		HEATING (Btu/Hr):	
Rated:(Min/Max):	15,000 (5,800 / 18,400)	47° Rated:(Min/Max):	18,300 (/)
Sensible AHRI:		17° Rated:	Add MSS
Moisture Removal (Gal/Hr):		5° Max:	Add MSS
Standard Operating Range:	50°F - 115°F	Operating Range:	-13°F - 60°F
Extended Operating Range:	-4°F - °F	47° Rated Heating Conditions:	Indoor (°F DB/WB): 70 / 60 Ambient (°F DB/WB): 47 / 43
Rated Cooling Conditions:	Indoor (°F DB/DB): 80 / 67 Ambient (°F DB/WB): 95 / 75	17° Rated Heating Conditions:	Indoor (°F DB/WB): 70 / 60 Ambient (°F DB/WB): 47 / 43

ELECTRICAL			PIPING	
Power Supply (V/Hz/Ph): *See Engineering Manuals for other voltages.		*208-230 / 60 / 1	Gas Connection (in):	1/2
System MCA:		16.0	Liquid Connection (in):	1/4
System MFA:		20.0	Drain Connection (in):	5/8
Compressor RLA:			Max. Interunit Piping Length (ft):	98.5
Outdoor fan motor FLA:			Max. Interunit Height Difference (ft):	66
Outdoor fan motor W:			Refrigerant Pre-Charged Pipe Length (ft):	49.25
Indoor fan motor FLA:			Additional Charge of Refrigerant (oz/ft):	0.22
Indoor fan motor W:				
MCA: Min.circuit amps	MFA: Max.fuse amps	RLA: Rated load amps		
			FLA: Full load amps	W: Rated output watts




Submittal Data Sheet

21.0 SEER2, Heat Pump, Ductless ODU, 1.25 Ton, Daikin AURORA R-32
RXT15AVJU9

INDOOR SPECIFICATIONS				
COOLING - Airflow Rate (cfm):			HEATING - Airflow Rate (cfm):	
High:	2,097	Med:	High:	2,327
Low:		SuperLow:	Low:	
Sound Pressure (H) (dBA):	52		Sound Pressure (H) (dBA):	57
Dimensions (HxWxD) (in):	29-1/2 x 31-1/4 x 12-5/8		Net Weight (lb):	113

DIMENSIONAL DRAWING - INDOOR UNIT

RXT15/18AVJU9



3D150942




Submittal Data Sheet

21.0 SEER2, Heat Pump, Ductless ODU, 1.25 Ton, Daikin AURORA R-32
RXT15AVJU9

OUTDOOR SPECIFICATIONS			
COOLING - Airflow Rate (cfm):		HEATING - Airflow Rate (cfm):	
High:	2,097	High:	2,327
SuperLow:		SuperLow:	
Compressor Stage:	Inverter	Refrigerant Type:	R-32
Factory Charge (Lbs):	2.45	Refrigerant Oil:	
Sound Pressure Level (dBA):	52		
Dimensions (HxWxD) (in):	29-1/2 x 31-1/4 x 12-5/8	Net Weight (lb):	113

DIMENSIONAL DRAWING - OUTDOOR UNIT

RXT15/18AVJU9



3D150942



Submittal Data Sheet

21.0 SEER2, Heat Pump, Ductless ODU, 1.25 Ton, Daikin AURORA R-32
RXT15AVJU9

ACCESSORIES

PART NUMBER	DESCRIPTION	INCLUDED
DACA-WB-3	Powder-Coated Wall-Mounted Bracket	No
KEH064A41	Drain Pan Heater	No
KPS063A41	Snow hood (intake side plate) (15, 18 & 24)	No
KPS063A44	Snow hood (intake rear plate) (15,18 & 24)	No
KPS063A47	Snow hood (outlet) (15, 18 & 24)	No
KPW063B4	Air direction adjustment grille	No